



Representative Image

Catalog No. 2TLA050011R1524

Description: MKEY8Z SS SOL NPT 230V SS FLX KEY

UPC No 804325833516

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, stainless steel housing and head, spring lock (power to unlock), 2000N holding force. 230VAC coil, 2NC+ 1NO(locke)d+2NC+ 1NO (actuator inserted). 3x 1/2NPT conduit entries. Delivered with stainless steel flex key.

Descriptors

Category	Safety Sensors, Switches, Locks & Gate Boxes
Type	Safety Lock

Specifications

Product Class	Safety Locks & Process Locks
Product Main Type	MKey
Supply Voltage	230VAC
Outputs	Contact
Number of Outputs	4NC + 2NO
Degree of Protection	IP67, IP69K

Classifications

ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking

Dimensions

Product Net Depth / Length	47 mm
Product Net Height	177 mm
Product Net Width	48 mm
Product Net Weight	0.867kg

Safety Information

Performance Level	Up to e
-------------------	---------

by ABB